





Superceded by D2057 rev B
KE 94.08.19 ISRA1229



GENERAL NOTES:

1. BEND RADIUS FOR 2024-T3 .063 THICK IS .188
2. PAINT -101 MATTE BLACK.
3. TYPE 304 STAINLESS STEEL MAY BE SUBSTITUTED WITH TYPES 303 OR 316.
4. 2024-T3 MAY BE SUBSTITUTED WITH 2024-T3 CLAD (QQ-A-250/5).

-103 FINISH: POWDER COAT BLACK SANDTEX (43537) PER DART QSI 003 4.3

FE-032-EF (QTY 4)
INSTALL PER PEM INSTALLATION INSTRUCTIONS.

UNDER REVIEW
08.05.27
-103/-104 TO HAVE 0.049" WALL

RELEASED
04.02.03

QTY. REQUIRED		PART NO.	ITEM	DESCRIPTION	MATERIAL	SPEC./VENDOR
	4	FE-032-EF		FASTENER		PEM
		D 2010-113		CLAMP	.050 THICK 3	AISI 304
		D 2010-111		SADDLE	.025 THICK 3	AISI 304
1		D 2010-109		PLUG	6061-T6 BAR	QQ-A-225/6
X		D 2010-103		ARM	CRES TUBE .50 DIA x .035W	AISI 304
4	X	D 2010-101		BRACKET	2024-T3 .063 THK	QQ-A-250/4
-103 - 101						

REVISION	DRAWN	APPROVED	DESCRIPTION OF CHANGE
C2	BRADLEY 90/12/15		
C1	KE		
C	KE		
B			
A			

THIS DRAWING IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR ANY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT THE PERMISSION OF DART AERO SYSTEMS INC.

REQUIREMENTS — UNLESS OTHERWISE SPECIFIED

GENERAL:
1. DIMENSIONS ARE IN INCHES
2. SURFACE ROUGHNESS 125
3. REMOVE SHARP EDGES .016 MAX.
4. THREADS PER MIL - S - 7742
5. HOLES PER AND 10387

LIMITS:
1. TOLERANCES — .XX ± .030, .XXX ± .010
2. ANGLES ± 1/2°
3. PARALLELISM ± .0025
4. ECCENTRICITY .005 MAX.
5. SYMMETRY ABOUT ALL M/C CENTRE LINES .005

REPORT ALL DISCREPANCIES — DO NOT SCALE

RIVET CODE SHALL BE PER NAS 523
BASIC CODE — DIA. DASH NO. N=HEAD NEAR SIDE F=HEAD FAR SIDE
D=DIMPLE C=COUNTERSINK — LENGTH DASH NO. W=SPOTWELD

BASIC CODES
BJ=MS20470AD
BB=MS20426AD

INST'LN.	MODEL	REGN	SER. NO

EFFECTIVITY

APPROVAL

CONTRACT NO.

		DATE
DRAWN	BRADLEY	90.03.31
DESIGN	BRADLEY	90.03.31
STRESS		
CHECKED		
CLIENT		

DART AERO ACCESSORIES INC.
VANCOUVER CANADA

TITLE: MIRROR BRACKET DETAILS

CODE | DWG. NO. D2010 | REV. C | SCALE NOTED | SHT 1 OF 1

D2010